

DS-66104



10.4" LCD All-in-One Player

Product Preview

A compact and rugged solution that features our reliable DV-66B MPEG-2 Player linked to a crisp 10.4" TFT LCD display. The DS-66104 can store and playback full-motion audio/video clips from high speed CompactFlash® memory cards (CF) with DVD quality audio/video output; MPEG-1, MPEG-2, JPEG, and MP3 file formats. This unit is small and light enough to be wall mounted or integrated into a full size kiosk. A high quality hardware solution at an affordable price. The unit is available with or without a touch panel.

DS-66104 - w/out touch screen feature.

DS-66104T - with touch screen, see touch screen specification.

Features

- 10.4 " TFT LCD display
- Support multiple formats: MPEG-2, MPEG-1, MP3, and JPEG
- Support Video, VGA, and S-video input.
- Repeat or Menu modes available
- Instant track response and Multiple track selection, up to 99 tracks
- Built-in stereo speakers
- RS232 TTL level (4800 Baud Rate) controllable
- Support stereo audio output
- Support PIR sensor connection
- Support 16:9 file format
- 44 pin connector for 2.5" hard disk (DV-66B)

Specifications

System Type	Digital Audio/Video playback
Format	MPEG-1 (VCD), MPEG-2 (DVD), JPEG, MP3
Dimension	W/housing: 11.25" (L) x 7.812" (W) x 1.812" (H)
Power Consumption	15W
Power Supply	Universal Switching Power Supply Input 100/240V, output DC 12V/3A
Operating Current	1.25A @12V
Operating Voltage	12VDC
Video Input	Video, VGA, and S-video input
Video Output	NTSC/PAL, Composite, VGA (DV-66B), and S-video (DV-66B)
Audio Output	Stereo (line level)
Storage Format	MPEG-2 files require High Speed CompactFlash Card min. (40X or up) MPEG-1, MP3, and JPEG files require a regular CF card Compact Flash cards must be FAT16 or FAT formatted
Max Memory	512 MB and up CompactFlash or MicroDrive

Benefits

- Long term durability - no moving parts
- Low maintenance - no tape to rewind
- Compact design - easy to install
- Reliable storage - re-programmable CompactFlash® media
- A high cost effective multimedia hardware solution
- Available in thermoplastic housing or board level

Applications

- POP displays
- Digital signage systems
- Interactive kiosks
- Mobile kiosks solutions

Accessories

DV-66K, Keypad Controller

To connect and control the DV-66B player with an external input device, such as push buttons.

DV-66U, Universal Controller

To connect DV-66 player with an analog touch screen. Eight switch buttons per controller. PIR supported.

High Speed Compact Flash® cards

For best result with the DS-66104, MedeaWiz recommends using 40X high speed CompactFlash® media cards.



933 Canada Ct., City of Industry, CA 91748

Corporate: 626-839-1488 • FAX: 626-839-7038

www.medeawiz.com • Email: sales@medeawiz.com

